


PIM Detection, Location and Mitigation

OneAdvisor 800 Wireless

Passive Intermodulation Overview


Passive intermodulation (PIM) has been one of the most common and recurrent problems in cellular networks, particularly in mobile services with a frequency division duplex (FDD) communication mode where PIM signals interfere with mobile transmissions (uplink).

PIM is created when multiple signals, such as when sub-carriers of LTE or 5G radios are transmitted over RF elements with nonlinear characteristics, in which case those signals get mixed into passive components generating intermodulation signals that might be at the same frequency as the uplink channel, which results in interference.



The impact of PIM interference in mobile networks is determined by the sensitivity of the radio in the mobile transmission (uplink) band. The sensitivity level of radios defined by 3GPP are as follows:


Technology	Cell-site Radio	Sensitivity (dBm)
GSM/EDGE (3GPP TS 45.005)	Normal BTS	-104.0
	Pico BTS P1	-88.0
CDMA (3GPP2 C.S0010-D)	Macro Cell (bands 450 and 800)	-117.0
	Macro Cell (band 1900)	-119.0
	Pico Cell	-117.0
WCDMA (3GPP TS 25.104)	Wide Area BS	-121.0
	Medium Range BS	-111.0
	Local Area / Home BS	-107.0
LTE (3GPP TS 36.104)	Wide Area BS (5, 10, 15, 20 MHz)	-101.5
	Local Area BS (5, 10, 15, 20 MHz)	-93.5
5G NR (3GPP TS 38.104)	Wide Area (5, 10, 15 MHz with SBC of 15 KHz)	-101.7
	Wide Area (20 to 50 MHz with SBC of 15 KHz)	-95.3
	Wide Area (20 to 100 MHz with SBC of 30 KHz)	-95.6
	Medium Range (5, 10, 15 MHz with SBC of 15 KHz)	-96.7
	Medium Range (20 to 50 MHz with SBC of 15 KHz)	-90.3
	Medium Range (20 to 100 MHz with SBC of 30 KHz)	-90.6
	Local Area (5, 10, 15 MHz with SBC of 15 KHz)	-93.7
	Local Area (20 to 50 MHz with SBC of 15 KHz)	-87.3
	Local Area (20 to 100 MHz with SBC of 30 KHz)	-87.6



1364.900.0123


PIM signals and Base Station Sensitivity Levels

The adoption of LTE and 5G NR signals with broadband channels are also susceptible to PIM which creates a broadband PIM signature with a distinct slope due to multiple mixing products of sub-carrier signals.



1365.900.0123

PIM signals and Base Station Sensitivity Levels



1366.900.0123

1367.900.0123

PIM Interference signature in broadband uplink channels


In addition, these new technologies have also incorporated multi-input multi-output (MIMO) technology enabling coverage and capacity with a massive antenna array, but adding more passive components into the cell site creates more possible instances of PIM.

In order to reduce this interference, it is very important to perform strict PIM testing during cell site deployment and maintenance on passive components, including antennas, feedlines, connectors, filters, diplexers, couplers, attenuators, among other; as well as objects in front of antennas, roofing materials, galvanic corrosion, metal snap-in hangers, hose clamps, metal strut fasteners, angle adapters, etc.


PIM Verification

PIM can be tested with VIAVI OneAdvisor 800 which is the ideal portable test solution to verify and troubleshoot 4G and 5G radio access networks for proper deployment and effective operation.

The PIM verification process includes two key elements, PIM Detection and PIM Location. It's process is described as follows:



OneAdvisor 800



1368.900.0123

PIM Verification Process

PIM Detection

There are two main phases and methodologies for PIM detection:



RfCPRI analysis: provides a realtime spectrum visibility of the uplink channel, via CPRI links, to identify any possible interference.




Realtime Spectrum Analysis (RTSA): provides a realtime persistent spectrum visibility of the uplink over-the-air.

PIM Detection with RFoCPRI

RFoCPRI technology performs RF measurements through the fiber fronthaul which is the link between base band units and remote radio heads.

RFoCPRI verifies the control signals and extracts the RF (IQ) data transmitted between the BBU and RRU at the ground without the need to climb the tower.



1068.9011222


OneAdvisor 800 PIM Detection with RFoCPRI Technology

In the presence of PIM in the uplink, it is required to perform a PIM Finding to eliminate PIM.

PIM Detection with RTSA

OneAdvisor 800 real-time spectrum analysis (RTSA) can be equipped with a PIM Probe and uplink filters, and the real-time spectrum can be set with a sound indicator based on a maximum power limit, which will automatically generate a sound and a FAIL indicator in the presence of PIM.

For TDD signals (LTE or 5G) it requires a different measurement technique than conventional spectrum analysis, since the uplink and downlink signals are transmitted on the same frequency, but in different timeslots. The OneAdvisor 800 can perform a TDD Auto-Gated Spectrum (TAGS), effectively conducting real-time spectrum measurements triggered only on the flexible symbols, or the timeslots assigned for uplink transmission.



1369.900.0123


Real-time Spectrum (FDD or TDD) for PIM Detection

PIM Location

The PIM Finding process can be simplified in three main steps:

1. PIM Location: Identify whether the PIM source is external (after the antenna) or internal (before the antenna)
2. PIM External: Conduct best practices to identify, eliminate or avoid external PIM sources.
3. PIM Internal: Conduct best practices to identify and eliminate internal PIM sources.

PIM External or Internal



1370.900.0123

PIM Verification Process – PIM External or Internal

To determine if the PIM source is external (after the cell site antenna) or internal (before the cell site antenna), PIM Absorbers are necessary to conduct a PIM Detection test.

PIM Absorbers are designed to be secured to the front face of base station antennas and suppress forward radiation from the antenna with minimum PIM generation and minimum reflection back into the antenna feed system.



PIM Absorber


OneAdvisor 800 (RFoCPRI™) PIM Detected



Antenna without PIM Absorbers and PIM blankets with PIM detected

1374.900.0123

OneAdvisor 800 (RFoCPRI™) PIM Not Detected




Antenna with PIM Absorbers and PIM blankets with PIM not detected

1373.900.0123

If PIM detection (RFoCPRI™) does not show PIM interference after the PIM Absorbers and PIM Blankets are installed in the antenna then it can be concluded that the PIM source is external (after the antenna). Likewise, if PIM detection (RFoCPRI) still shows the presence of PIM then a PIM source is internal (before the antenna).

PIM Internal




PIM Verification Process – PIM Internal

Multiple internal PIM sources might exist in the cell site, for which a PIM inspection is required to assess for any of the following:

- Inspect cables and antennas for possible damage
- Inspect for possible corrosion or rust on RF connectors and mounting structure including metal clamps and support brackets.
- Inspect whether RF connections have been properly tightened, and tap on the feed-line to see if PIM is detected with RFoCPRITM.

PIM External



PIM Verification Process – PIM External

External PIM can be generated from multiple sources. Therefore, a series of tests using a PIM Probe are required, specifically placing a PIM Blanket and/or a PIM Foil in potential PIM source locations, especially where metal elements lie in close proximity to the radio antenna.

A PIM Probe is used in conjunction with OneAdvisor 800 real-time spectrum to precisely locate external PIM sources in the field.


- PIM Probe frequency range: 600 MHz to 4000 MHz
- OneAdvisor 800 real-time spectrum with RF power level sound indicator

If a PIM source is found, then cover it with a PIM Blanket or PIM Foil and verify it with the PIM Probe and RFoCPRI™.

PIM Blankets are temporary RF barriers that can be deployed to help isolate sources of PIM. When a PIM Blanket is placed over an external PIM source, PIM from that source is typically reduced by >30 dB.

A PIM Foil is a light weight RF barrier making it easier and faster to cover large areas at rooftop cell sites. A PIM Foil is recommended when wind speeds > 10 mph.

Once PIM locations are identified, mitigation materials can be applied to reduce the PIM levels and improve site performance.




PIM Probe and OneAdvisor 800

1375.900.0123



1376.900.0123



1377.900.0123

Test Process Automation with Job Manager and StrataSync

VIAVI Test Process Automation allows RF technicians to perform installation and maintenance tests with confidence:

- In accordance with mobile operator's test criteria
- Covering all radio types and topologies
- Automatically uploading test results to the StrataSync cloud with simple PASS/FAIL indicator


Job Manager

The VIAVI Job Manager automates test processes, offering mobile network operations and construction teams a self-guided test solution, improving efficiency in the field for radio site installation and maintenance.

Job Manager's automates the entire process ensuring the proper test sequence is executed according to mobile operator's requirements, configuration test time is minimized, and results are consistent and consolidated.



Job Manager



Test Type	Reference Info	Status
CAA Reflection VSWR	Sector: Alpha , Band: 600 , Cable: HFC-12D (1/2) , Termination: Load	To Do
CAA DTF VSWR	Sector: Alpha , Band: 600 , Cable: HFC-12D (1/2) , Termination: Load	To Do
Fiber Inspection	Cable: Alpha Sector , Connector: DL	To Do
CAA Reflection Return Loss	Sector: Beta , Band: 600 , Cable: HFC-12D (1/2) , Termination: Load	To Do
CAA DTF Return Loss	Sector: Beta , Band: 600 , Cable: HFC-12D (1/2) , Termination: Load	To Do

Test Type	Reference Info	File	Verdict
RT Persistent Spectrum		Test1.png	N/A
CAA Reflection VSWR		t1.png	N/A
CAA Reflection VSWR		t2.png	N/A
RT Persistent Spectrum		Test2.png	N/A
RF Sweep Tuned Spectrum		Test3.png	N/A
RT Persistent Spectrum		Test4.png	N/A
RT Persistent Spectrum		Test5.png	N/A
RT Persistent Spectrum		Test6.png	N/A
RT Persistent Spectrum		TEST-A.png	N/A
RT Persistent Spectrum		TEST-B.png	N/A
CAA Reflection VSWR		CAA-1.png	N/A

1129.900.0522


OneAdvisor 800 Job Manager

StrataSync

VIAVI StrataSync is a cloud-hosted system that provides a centralized management of test solutions including test set management, test configurations, data management, and test results.

StrataSync is designed to eliminate email dispatches, manual test procedures, manual report consolidation, test solution availability and test devices that need calibration.

VIAVI StrataSync enabled



Asset class	Asset Type	Model	Serial No	Tech ID	Asset Status	Firmware	HW Version	
<input type="checkbox"/>	Syncable	CellAdvisor CAA	JD723C	BEF31069	rftest1234	Active	1.066.001	1.000
<input type="checkbox"/>	Syncable	CellAdvisor BSA	JD745B	EFA41184	rftest1234	Active	3.110.023	4.000
<input type="checkbox"/>	Syncable	CellAdvisor BSA	JD745B	GAH41868	rftest1234	Active	3.110.025	4.000
<input type="checkbox"/>	Syncable	CellAdvisor 5G	CA5000	CASN003	rftest1234	Active	5.055.025v-1	004
<input type="checkbox"/>	Module	CellAdvisor 5G-module	Advisor SHIM	WHAK0041490005	rftest1234	Active		004
<input type="checkbox"/>	Module	CellAdvisor 5G-module	4136 MA3FCO	00791	rftest1234	Active		16
<input type="checkbox"/>	Module	CellAdvisor 5G-module	Advisor SHIM	WHAK0052090001	rftest1234	Active		005
<input type="checkbox"/>	Module	CellAdvisor 5G-module	4146 QJAD	34208	rftest1234	Active		27
<input type="checkbox"/>	Syncable	ONA-800	ONA-800	WMSR0011600010	rftest1234	Active	1.2.0-79d5204.	008
<input type="checkbox"/>	Module	ONA-800-module	4146 QJAD	36061	rftest1234	Active		27
<input type="checkbox"/>	Module	ONA-800-module	IDB-SA	WMSG0042000020	rftest1234	Active		004
<input type="checkbox"/>	Module	ONA-800-module	ONA-800A-DISPL	WMSG0021600010	rftest1234	Active		002

1130.900.0522

StrataSync – Asset Management



1129.900.0522

Ordering Guide







OneAdvisor 800 Wireless

OneAdvisor 800 Bundles with RFoCPRI and RTSA:

- **ONA800A-SPCP**
- **ONA800A-SPCPA**
- **ONA800A-SPCPAOS**
- **ONA800A-SPCPAOS-A**



Example: ONA800A-SPCP-CBF

PIM Accessories	CBF	CBK	CA	CBFA	CBKA
 PIM Blanket 60 in (1.52 m) 60 in (1.52 m)	■			■	
 PIM Foil 36-Inch x 100-FT Roll	■			■	
 PIM Blanket Kit 3x 120x60, 2x 60x60		■			■
 PIM Absorber Kit Case (2) + Front Absorber + Back Absorber			■	■	■

References

- ITU-T K.149: Passive intermodulation test methods of array antenna systems in mobile communication systems
- ConcealFab Interference 2022 Product Guide



Contact Us **+1 844 GO VIAMI**
(+1 844 468 4284)

To reach the VIAMI office nearest you, visit [viavisolutions.com/contact](https://www.viavisolutions.com/contact)

© 2023 VIAMI Solutions Inc. Product specifications and descriptions in this document are subject to change without notice. Patented as described at [viavisolutions.com/patents](https://www.viavisolutions.com/patents) pim-oneadvisor800wireless-an-xpf-nse-ae 30193709.900.0323