Data Sheet



VIAVI

T-BERD/MTS-2000 Handheld Modular Test Set

Fiber Optic Multitest Tool for Smarter, Faster Field Testing

Costs, workflow, quality, network performance, and customer experience are critical for the success of today's fiber optic networks. Selecting the right test tools has become key toward meeting these needs. The VIAVI Solutions™ T-BERD®/MTS-2000 is a handheld multi-test platform that provides field technicians with a single handheld unit to install, turn-up and maintain these networks to the highest standards.

VIAVI T-SERI

T-BERD/MTS-2000

Its innovative design and hands-free bag ensure that all essential fiber test tools are close at hand, whatever the job or location. A large color screen with graphical user interface drives simple operation and optimal workflow in the field

Test capabilities include a range of OTDR modules for multimode and single-mode testing, including CWDM & DWDM OTDR, as well as a range of FiberComplete™ modules for automated insertion loss/optical return Loss (IL/ORL), OTDR and fault finding. Both OTDR and FiberComplete modules are passive optical network (PON) optimized. The unit is also ready for connector end face pass/fail analysis to IEC standards with a digital analysis microscope.

The CWDM-OSA and DWDM-OCC modules also enable turn-up and troubleshooting of coarse or dense wavelength division multiplexing (CWDM DWDM or Hybrid) networks.



VIAVI StrataSync enabled

Key Benefits

- Ensure the highest-quality connectorizing, splicing, and turn-up of new fiber links
- Improve workflow with hands-free solution, driving best practices to IEC standards
- Smarter and faster field testing with simple setup and instantaneous pass/fail results
- Boost productivity with improved report generation and flexible connectivity
- Decrease OpEx and increase field productivity when combined with StrataSync™ and CerTiFi

Key Features

- High-visibility touch-screen display
- Wide range of field installable OTDR modules including QUAD and PON
- Optional built-in optical power meter, visual fault locator (VFL), and optical talk set
- Flexible connectivity with Ethernet, USB, Bluetooth®, and WiFi capabilities
- Smart Access Anywhere (SAA) for remote control and field tech support
- StrataSync enabled centralized cloud based asset, configuration, test data and workflow management



Applications

- Fiber optic test, qualification, certification and reporting
- Certify the fiber physical layer on FTTx/ PON, access, metro and enterprise networks
- FiberComplete automated uni and bidirectional IL, ORL, Length, OTDR certification
- Automated fiber inspection and IEC pass/fail analysis

Widest Range of Applications for Maximum Flexibility

The T-BERD/MTS-2000 provides the largest range of test capabilities offered in one handheld unit. The modular design allows service providers the maximum flexibility to scale their investment and evolve with the growth of their network.

The instrument supports the whole range of essential fiber analysis tools including connection inspection, connection check, source, ORL, OTDR, a power meter, and DWDM Optical Channel Checker (DWDM-OCC).

Application modules used with the T-BERD/MTS-2000 can also be used with the T-BERD/MTS-4000 V2 and the two products are interoperable.



Boosted Productivity with Seamless Data Workflow

The T-BERD/MTS-2000 integrates various communication capabilities allowing remote control, data and setup uploads/downloads, and report transfer. The unit has one high-speed 1G Ethernet port, three USB ports, and optional WiFi and Bluetooth network connections.



T-BERD/MTS-2000 Design Optimizes Operational Efficiency



- 1 5-inch touch screen
- 2 Charge indicator
- 3 On indicator
- 4 File menu
- 5 Setup menu
- 6 Start/Stop
- 7 Testing indicator
- 8 On/Off
- 9 Home page
- Cancel
- 1 Direction and validation keys

- Results page
- B Loudspeaker
- 14 Headset jack
- **15** AC/DC input
- 16 Slave mini USB port
- 17 RJ45 connector
- 18 Master USB ports (2)
- 19 Power meter port
- 20 VFL or talk set port
- 2 WiFi and Bluetooth options







StrataSync — Empower Your Assets

StrataSync Core capabilities are included when you purchase any StrataSyncenabled instrument from VIAVI, there is nothing to buy to take advantage of these benefits. StrataSync Core includes asset and configuration management, test data management with 35 day limit, and even instrument self-management for techs via the Tech Portal. StrataSync Plus extends test data storage for up to 6 years and provides access to seasoned VIAVI StrataSync experts for assistance with setup, config, usage, reporting – just about anything that you desire.

Specifications

General (typical at 25°C)				
Display	5-inch TFT color touch screen (12.5 cm) Resolution 800 x 480 WVGA				
Interfaces	Two USB 2.0 ports One mini-USB 2.0 port RJ45 LAN 10/100/1000 Mbps Built-in Bluetooth (optional) Built-in WiFi 802.11 b/g/n (optional)				
Internal memory	8 GB (1 GB for storage)				
Battery	Rechargeable lithium-polymer battery 9-hour operation as per Telcordia GR-196-CORE				
Power supply	AC/DC adapter, input 100-250 V AC, 50-60 Hz; 2.5 A max, output 12 V DC, 25 W Electrical safety: EN60950-compliant				
Size with module (H x W x D)	175 x 138 x 80 mm (6.9 x 5.4 x 3.2 in)				
Weight with battery with battery and LM OTDR	0.864 kg (1.89 lb) 1.21 kg (2.67 lb)				
Operating temperatures No options/modules With options/modules	-20 to +50°C (-4 to 122°F) 0 to +40°C (32 to 104°F)				
Relative humidity	0% to 95% noncondensing				
Built-In Power Meter ¹					
Calibrated wavelengths	850/1310/1490/1550/1625/1650				
Wavelength range	800 to 1650 nm in 1 nm steps				
Accuracy ²	±0.2 dB				
Measurement range ³	+5 to -50 dBm				
Maximum resolution	0.01 dB/0.01 nW				
Connector type	Universal push pull (UPP)				

- 1. At 25°C, after 20 minutes stabilization time and after zero setting.
- 2. At calibrated wavelength (except 1650 nm)
- 3. -45 dBm from 800 to 1250 nm

Built-In Visual Fault Locator (VFL)						
Wavelength	650 nm					
Emission mode	CW, 1 Hz					
Laser class	Class 2 per standards EN60825-1 and FDA21 CFR Part 1040.10					
Built-In Talk Set						
Dynamic range	ange 32 dB (typical)					
Connector types	SC, FC, and UPP (three adapters included)					

Ordering Information

Description	Part Number		
T-BERD/MTS-2000 Handheld Modular Test Set Includes: touch screen, hands-free soft case, shoulder strap, power supply with 5 adaptable plugs (US, Europe, UK, Australia, Japan), on-line Getting Started manual	ETB2000HVT/ EM2000HVT		
Built-in optical power meter and VFL, with 2.5 mm UPP connectors	E20PMVFL		
Built-in optical power meter with 2.5 mm UPP connector	E20PM		
Built-in visual fault locator (VFL) with 2.5 mm UPP connector	E20VFL		
Built-in optical power meter and talk set	E20TSPM		
Internal Bluetooth option	E20BLUE		
Internal WiFi option	E20WIFI		
USB2.0 digital video scope kit (P5000i), including 7 tips and soft case	EDFSCOPE5Ki		
Soft carrying case for T-BERD/MTS-2000/4000	E40SCASE1		
Hard carrying case for T-BERD/MTS-2000 Modular Test Set	E20HCASE		
12 V car adapter for T-BERD/MTS-2000/4000	E40LIGHTER		

VIAVI Care Support Plans

Increase your productivity for up to 5 years with optional VIAVI Care Support Plans:

- Maximize your time with on-demand training, priority technical application support and rapid service.
- Maintain your equipment for peak performance at a low, predictable cost.

Plan availability depends on product and region. Not all plans are available for each product or in every region. To find out which VIAVI Care Support Plan options are available for this product in your region, contact your local representative or visit: <u>viavisolutions.com/viavicareplan</u>

Features *5-year plans only

Plan	Objective	Technical Assistance	Factory Repair	Priority Service	Self-paced Training	5 Year Battery and Bag Coverage	Factory Calibration	Accessory Coverage	Express Loaner
BronzeCare	Technician Efficiency	Premium	√	✓	✓				
SilverCare	Maintenance & Measurement Accuracy	Premium	✓	✓	√	√ *	✓		
MaxCare	High Availability	Premium	✓	✓	✓	√ *	√	√	√



Contact Us

+1 844 GO VIAVI (+1 844 468 4284)

To reach the VIAVI office nearest you, visit viavisolutions.com/contact

© 2021 VIAVI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
Patented as described at viavisolutions.com/patents t-berd-mts-2000-ds-fop-tm-ae 30168463 908 0721