

IXIA NET TOOL OPTIMIZER® 5236

ENTERPRISE-CLASS NETWORK MONITORING SWITCH

The Net Tool Optimizer (NTO) 5236 intelligent network packet broker provides high-density performance and 10GE visibility for network monitoring tools in all parts of a fiber network. The 5236 offers up to 24 SFP/SFP+, four 10/100/1000 copper Ethernet ports, and the industry's most advanced, easy-to-use, drag-and-drop control panel.

The NTO 5236 is available in a 10GE version or a 1GE fiber optic version. The NTO 5236 includes two module slots to allow the addition of up to four additional 10GE ports using the 5200 Series expansion modules. Modules are available for standard ports or as Advanced Feature Modules (AFMs) to support hardware-based advanced packet processing.

PRODUCT FEATURES

Port Flexibility

- Up to 28 ports available
- Ports 1-20: 1GE (SFP) or 10GE (SFP+)
- Ports 21-24: Up to 1GE copper
- Modular Ports 1-4: 1GE SFP or 10GE SFP+
- ZERO-loss advanced packet processing (Requires optional AFM)
- Port tagging
- Monitoring tool port load-balancing
- Filtering
- Advanced Packet Processing
- Regulatory/Safety
- RoHS Compliant

HIGHLIGHTS

- 10MB to 10GE Ethernet support
- Non-blocking architecture; 244Gbps total bandwidth
- Up to 28 ports available
- SNMP v1, v2, v3 support
- Centralized filter templates
- Custom dynamic filtering
- ZERO-loss packet processing

PRODUCT CAPABILITIES

FILTERING

- Centralized filter templates
- Custom dynamic filtering
- Overlapping Filter Engine
- Filter parameters (Layer 2-4)
- MAC Source/Destination addresses
- VLAN and Ethertypes
- IP protocol and DSCP/TOS
- Source/Destination IP (IPv4/IPv6)



UDP, TCP Ports

ADVANCED PACKET PROCESSING (REQUIRES OPTIONAL AFM)

ZERO-loss packet processing

Use any combination of supported features without performance impact

Supported Features:

- De-duplication
- Packet trimming
- Protocol stripping (GTP, MPLS, VLAN, VNTAG)
- Gigabit extended burst protection
- Timestamping

REGULATORY/SAFETY

NORTH AMERICAN SAFETY

UL 60950-1, 2nd Edition

CSA C22.2 No. 60950-1, 2nd Edition EMI/EMC

NORTH AMERICAN EMC

FCC part 15, Class A (USA)

ICES-003 Issue 4, Class A (Canada)

EUROPEAN EMC

EN55022 2003 Class A (Emissions)

EN55024 1998 w/A2 (Immunity)

EN61000-3-2:2006 (Harmonics)

EN61000-3-3 1995 w/A2 (Flicker)

IEC/INTERNATIONAL EMC

IEC/EN 61000-4-2:2001 Electrostatic Discharge Immunity

IEC/EN 61000-4-3:2002 Radiated Immunity

IEC/EN 61000-4-4:2001 Transient/Burst Immunity

EN61000-3-3 1995 w/A2 (Flicker)

IEC/EN 61000-4-5:2001 Surge Immunity

IEC/EN 61000-4-6:2001 Conducted Radio Frequency Immunity

IEC/EN 61000-4-11:2004 Voltage Dips, Interruptions and Variations

SPECIFICATIONS

GENERAL SPECIFICATIONS	
<p>Performance</p> <ul style="list-style-type: none"> • 10MB to 10GE Ethernet support • Non-blocking architecture; 244Gbps total bandwidth • Full line rate across all ports with filtering enabled • Port reconfiguration with no performance impact 	<p>Management</p> <ul style="list-style-type: none"> • SNMP v1, v2, v3 support • TACACS+, RADIUS, and Local support (members and groups) • Granular access control features • Event logging • Syslog • IT Automation control (RESTful API) • IP based management port (RJ45 10/100/1000)
PHYSICAL SPECIFICATIONS	
<p>NTO 5236 Size and Weight</p> <ul style="list-style-type: none"> • 1U high 19 rack mountable enclosure • Dimensions: 17.5W x 19L x 1.75H (inches) • Weight: 15.5lb (7 kg) <p>Included Accessories</p> <ul style="list-style-type: none"> • AC power cord • USB flash drive with activation license key • Rack mount kit 	<p>Power for NTO 5236 Option (AC)</p> <ul style="list-style-type: none"> • Input AC Voltage: 90-240 VAC RMS auto-switching • Frequency: 50-60Hz • Nominal power requirement: 1.27A @ 110 VAC, 140W • Maximum power requirement: 3.2A @ 110 VAC, 353W • Heat/Power Dissipation: nominally 140Watts /478 BTU/hour <p>Power for NTO 5236 Option (DC)</p> <ul style="list-style-type: none"> • Input DC Voltage: 12V DC • Nominal power requirement: 10A @ 12 VDC, 120W • Maximum power requirement: 25A @ 12 VDC, 300W

OPERATING SPECIFICATIONS

<p>Temperature</p> <ul style="list-style-type: none"> Operating temperature: 0 to 40 C 	<p>Humidity</p> <ul style="list-style-type: none"> Operating humidity: 10 to 85%, noncondensing Fans: Automatic temperature-controlled DC fans (right to left airflow)
--	---

PRODUCT INFORMATION

PRODUCT DESCRIPTION

<p>NTO 5236 base system - with all 24 10G and 4 Copper ports licensed</p>
<p>NTO 5236 System with 24 10G and 4 Copper ports licensed - with 20G of AFM</p>
<p>NTO 5236 System with 24 10G and 4 Copper ports licensed - with 40G of AFM</p>
<p>NTO 5236 base system - with all 24 1G and 4 Copper ports licensed</p>
<p>1GE SFP+ port - quantity One (transceiver not included)</p>