

VIAVI TeraVM

TeraVM 5G NSA Core Emulator



Overview

The VIAVI TeraVM Core Emulator adds to the capabilities of the industry- standard TM500 Test Mobile to provide a full wrap-around test of a 5G gNB for 5G Non-standalone (NSA) mode.


One of the biggest challenges facing NEMs and mobile operators as they launch 5G is developing products against constantly changing and maturing 3GPP specs.

TeraVM Core Emulator can remove the pain of Core Network dependencies by giving RAN engineers a controllable and repeatable test environment that helps implement 3GPP standards rapidly and simplify the development lifecycle of 5G gNBs and the introduction of 5G services to the market.

Features

- First to market alignment with 3GPP standards
- Runs in lightweight VM on standard x86 hardware
- Automation and scripting tools
- Negative testing via error generation on S1-MME interface.
- Alignment and compatibility with TM500 Test Mobile
- One-stop test support
- View all Core Network KPIs on one GUI







Testing Throughout the gNB Lifecycle

The VIAVI TM500 UE Emulator is already extensively used throughout the R&D lifecycle for functional, system integration, capacity and regression testing. It is also used by network operators for debugging networks or evaluating network performance prior to launch of new services. Control of the gNB under test can be done by connecting it to a real or test Core Network though increasingly engineers prefer to use a core network emulator to implement standards rapidly as it makes it less problematic. A real or test Core Network can prove expensive and requires dedicated engineers to manage it. As a result, RAN engineers prefer an emulated core where they maintain control of their own test resource.

Benefits of Emulated Core Network

- Time to Market Alignment and compatibility with TM500 and gNB 3GPP specifications, making it easier to identify and pinpoint issues
- Agile Releases Releases made bi-weekly with common configuration with TM500
- Remote software upgrades
- Ease of access. RAN engineers have access to an always available Core Network test resource thereby boosting test productivity.
- Controllable: a single shared Core may not be set up in line with a particular set of RAN test requirements. The TeraVM 5G Core Emulator can be configured to match specific RAN test needs.
- Repeatable: engineers managing a real/test Core need to make constant changes and updates to keep it
 up to date. But when debugging a gNB problem or trying to optimize performance, a constant/repeatable
 environment is required.
- Robust Testing: the TeraVM 5G NSA Core Emulator allows engineers to insert errors on the S1-MME interface to check the robustness of the qNB design.
- KPI overview view KPIs from all Core Network functions on 1 GUI screen
- Portability 1U Server based system, easy to transport and setup (Lab to Field)
- Lightweight Deploy and configure in real-time
- Deterministic Performance Outcome is always consistent.

Supported Features

	5G-NSA Option 3x Procedures
TVM-CORE	Attach procedure
	PDN Connection/Disconnection for gNB bearer
	RAB-Setup Procedure
	Modify RAB procedure
	Mobility from NSA coverage to 4G coverage

Error Generation via S1-MME Interface

Use TeraVM 5G NSA Core Network Emulator to generate errors via the S1-MME interface and observe how the gNB reacts. All protocol layers from IP over SCTP to NG-AP and NAS can be emulated. Modification of messages and/or parameter on any protocol layer can be done using the TeraVM Core Emulator built-in error generation.

The following emulated error states are supported:

- Message Rejection
- Discard Silently
- Response Delay

The above flexibility allows the customer to decide which impairments they would like emulated and tested. VIAVI works with its customers to regularly update new error insertion scenarios.

"Pay as you grow" Architecture

TeraVM was designed from the start as a virtualized solution that runs on industry-standard servers. Virtualization gives customers the flexibility to scale TeraVM's performance to suit specific needs.

Starting from an entry level 1 Gbps capacity suitable for a new project start up or small cell supplier.

Automation and Scripting

The TeraVM Core Emulator comes with build-in management options, shell or a web client and provides APIs to control and operate the Emulator from external applications.

- Core Emulator shell
- Command Line Interface with readline/autocompletion support
- Fully scriptable

First to Market 3GPP Standards Test Alignment

VIAVI has the largest dedicated 4G and 5G R&D team of any test company focusing on gNB/eNB test. We work closely with our key customers to ensure that our roadmap is closely aligned to market needs and that we deliver test capability first. The TeraVM Core Emulator and TM500 Test Mobile follow a common 3GPP baseline to ensure that both deliver functionality early and that will work together smoothly.

One Stop Shop for Support

VIAVI TeraVM has a world class support team located close to customers that speaks the same language as them and is exceptionally highly trained. The same support team handle both TM500 and TeraVM products eliminating the frustrations of one vendor product blaming the other.

Specification and Configuration

The TeraVM 5G NSA Core Emulator consists of the following subcomponents and interfaces:

Subcomponents

MME (Mobility Management Entity)

- SGW (Serving Gateway)
- PGW (Packet Gateway)
- HSS (Home Subscriber Server)
- PCRF (Policy Control Rules Function)

Interfaces

- S1-MME
- S1-U

The implemented features are according to the following 3GPP specifications:

- System Architecture for the 5G System
- Procedures for the 5G System
- Non-Access-Stratum (NAS) protocol for 5GS
- NR and NG-RAN Overall Description
- NG Application Protocol (NGAP)
- NG-RAN; Xn general aspects and principles
- NG-RAN; Xn application protocol (XnAP)
- Study on New Radio Access Technology; Radio Access Architecture and Interfaces
- NG-RAN Architecture Description

Order Codes

TeraVM 5G Core Emulator is available with the following product codes:

Part Number	Description	Gbps	Support
48000/306	NSA 4G Core EM Base	Up to 10 Gbps	SA306
48000/307	NSA 4G Core EM 2.5 Gbps	2.5 Gbps step for NSAG Core Em	SA307
48000/316	Error Insertion Option	100 Gbps	SA316

For further details please visit: https://www.viavisolutions.com/en-us/products/teravm-5g-core-emulator

Also available as part of the TeraVM family of products is the 5G NSA and 4G core emulator package: https://www.viavisolutions.com/en-us/solutions/wireless/rantocore#tabs-network-application-traffic-emulation

