

QUICK CARD

Ethernet Layer 2 Bit Error Rate Test (BERT)

This quick card describes how to set up the OneAdvisor 800 as a Layer 2 Traffic Generator and measure Bit Error Rate (BER). The quick card documents a procedure to set up the OneAdvisor on a 1GigE Optical Interface, but the same workflow may be applied to other data rates.









EQUIPMENT REQUIREMENTS

- OneAdvisor 800 equipped with the following:
 - o RAXxMA-O Radio Analysis Module, SPA06MA-O Spectrum Analyzer Module, TM400GB-QQ 400G Module, or TM400GB-QO 400G Module.
 - o Transport software release V5.1.0 or greater
 - o CA10M1GE or ONA-SP-10M1GE 1 Gigabit Ethernet option
- Optical Transceiver supporting the Ethernet data rate to be tested (SFP, SFP+, SFP28, or QSFP28)
- Cables to match the optical transceiver and the line under test
- Fiber optic inspection microscope (P5000i, FiberChek Probe, or INX-760)
- Fiber optic cleaning supplies



Figure 1: Equipment Requirements

LAUNCH TEST

1. Press the Power button  on the ONA-800 base top panel to turn on the OneAdvisor.
2. Tap  to display the Home Screen.
3. Tap  to display the Tests menu.
4. Tap **Radio Analysis Transport >** or **400G Transport >** to show the Transport test application.
5. Tap the **Transport** icon. 
6. If the **Select Test** menu is not displayed, tap  in the lower left screen corner.
7. Using the **Select Test** menu or favorite test list, launch the Ethernet Layer 2 Traffic test for the desired data rate and port (P1 or P2). For example: **Ethernet ► 1GigE Optical ► Layer 2 Traffic ► P1 Terminate**.
8. If the current configuration is unknown, tap  to open the **Tools** Panel and select .
9. Press  to continue.




Figure 2: Transport Launch screen




Figure 3: Select Test

QUICK CARD

CONFIGURE TEST (CONTINUED)

► Select the **Ethernet** settings tab.

1. If you are testing a VLAN, set **Encapsulation** to **VLAN**, tap the **VLAN** field and enter your **VLAN ID**.
2. If you are testing head-to-head with another OneAdvisor or T-BERD:
 - Tap the **SA** field to display the Factory Default Source MAC Address. Provide this address to the operator of the other OneAdvisor or T-BERD upon request.
 - Tap the **DA** field and enter the Source Address (SA) of the far-end OneAdvisor or T-BERD in the **Destination MAC** field.
3. Tap the **Data** field, and set **Tx Payload** to **BERT**.
Note: This will disable Frame Loss and Round-Trip Delay results.




Figure 7: Setup, Ethernet/VLAN




Figure 8: Setup, Ethernet/DA




Figure 9: Setup, Ethernet/Data




Figure 10: Setup, Filters




Figure 11: Setup, Traffic

► Select the **Filter** settings tab and set **Encapsulation** to **None**. Set **Filters** to Ethernet, tap the **Type** field, and set **Ethertype** to 0700.

► Select the **Traffic** settings tab. Set **Load Unit** to **Bit Rate** and set **Load** to the desired traffic rate or Committed Information Rate (CIR).




► Tap the **Results** soft key.



QUICK CARD

CONNECT TO LINE UNDER TEST

► For Optical Interfaces:

1. Use the VIAVI P5000i or FiberChek Probe microscope to inspect both sides of every connection being used (SFP, attenuators, patch cables, bulkheads)
 - Focus the fiber on the screen.
 - If it appears dirty, clean the fiber end-face and re-inspect.
 - If it appears clean, run the inspection test.
 - If it fails, clean the fiber and re-run inspection test. Repeat until it passes.
2. If necessary, insert optical attenuators into the SFP TX and/or RX ports.
3. Connect the optical transceiver to the port under test using a jumper cable compatible with the line under test.
4. Select the **Laser** tab in the **Actions** panel.
5. Press . The button will turn yellow and be relabeled .
6. Press the **Restart** soft key .
7. Verify the following:
 - **Summary** LED is green.
 - **Signal Present** LED is green.
 - **Sync Acquired** LED is green.
 - **Link Active** LED is green.

► For 10/100/1000M Copper Interfaces:

1. Connect the copper SFP to the port under test using CAT5e or better cable.
2. Press the **Restart** soft key.
3. Verify the following:
 - **Summary** LED is green.
 - **Sync Acquired** LED is green.
 - **Link Active** LED is green.



Figure 12: Inspect Before You Connect








Figure 13: Optical Interface Results

QUICK CARD

LOOP UP AND RUN TEST

1. Select the **Actions** tab in the **Actions** Panel.
 - ▶ If you are testing head-to-head, to a hard loop, or if the loopback device is already in Local Loop Back (LLB) mode, proceed to step 2.
 - ▶ If the Loopback device is a OneAdvisor, T-BERD/MTS 5800 or another VIAVI compatible loopback device, tap  to loop up the far end device.
2. Tap . The button will turn yellow and be relabeled .
3. Press the **Restart** soft key  on the right side of the screen. Verify that the Right Results window shows “Rx Mbps, L1” approximately equal to the Committed Information Rate.
4. Using the drop-down menus, change the right results window to **Ethernet/BERT Stats**.
5. Allow the test to run for the desired duration. Verify that your **Bit Error Rate** is less than the Bit Error Rate threshold.

Notes:

- The **Summary/Status** window will turn red if there is a single bit error, regardless of the **Payload Error Rate** threshold.
- If the test traffic is transported through any Layer 2 or Layer 3 network equipment, including Ethernet Switches, Routers, NIDs, and Layer 2 Loopback devices, they will drop all errored frames. This will result in multiple **Bit Errors** and **Pattern Losses**.




Figure 14: Loop Up




Figure 15: Start Traffic




Figure 16: BERT Stats