

Calnex Paragon neo-S

Next-generation Sync Test: Interface rates to 800GbE

The cutting-edge test solution for synchronization testing – spanning NRZ to 800GbE.

Supporting Your Changing Environment

Driven by ever increasing 5G data demands and the performance requirements for AI workloads, the adoption of high-speed Ethernet continues to surge. As does the challenge of verifying packet synchronization for network equipment.

Building on the pedigree of the Calnex Paragon family, Paragon neo-S is the new, cutting-edge test solution for synchronization testing up to 800GbE. It's designed for the stringent test requirements of enhanced 5G and O-RAN timing standards as well as the developing requirements driving operational efficiencies in data centers.

What's more, because high network efficiency and reduced data transmission costs are only possible with highly accurate timing, Paragon neo-S offers hardware performance and software test methodologies allowing sub-nanosecond accuracy for the entire test system.

Paragon neo-S also offers unequalled compatibility. With step changes in physical layer technology needed for 800GbE, a new generation of pluggable optical transceivers are being created. Paragon neo-S not only meets the challenge of synchronization testing at 800GbE, but with the next generation of transceivers too.

Calnex is committed to providing the most advanced, precise and reliable test solutions to make sure your devices and systems deliver the high-quality network services of the future. In a changing world, it's good to know that some things never change.




Paragon neo-S

Analyse PTP conformance to standards-based or user-defined profiles, with automatic indication of pass/fail (and reason for non-compliance) and report generation.

Generate SyncE wander for ITU-T G.8262.1/G.8262 testing, simultaneously measure SyncE wander and PTP Time Error, and control ESMC message generation for testing to ITU-T G.8264.

Emulate PTP clocks to maximise accuracy and repeatability of PTP test, including specific test modes for various DUTs and automatic test selection for ITU-T and O-RAN standards conformance.





PTP Field Verifier (PFV)

- Analyze PTP protocol for conformance to standards or user-defined profiles.
- Automatic pass/fail indication – check captured PTP messages against a pre-defined set of rules, with clear pass/fail alerts.


Conformance Test Application

- Start testing in seconds – just two clicks to configure crucial standards-defined test sequences.
- Automatically generates PTP and ESMC messages, Time Error and SyncE impairments, and applies filters, metrics and masks.



Full Suite of PTP and SyncE Wander Testing

Simultaneously test PTP Time Error/SyncE wander and measure output packet timing, recovered clocks and SyncE wander, with unbeatable test accuracy and repeatability across rates, even up to 800GbE.




- Analyze the Time Error (TE) of, for example, Class-C/D T-Boundary Clocks or Class-B PRTC/Master Clocks.
- Apply standards-defined Time Error impairments.
- Combine with SyncE and ESMC for complex tests such as Phase Noise Response to SyncE Transient.


Application	Standard
Boundary Clock Testing	ITU-T G.8273.2
Transparent Clock Testing	ITU-T G.8273.2
APTS Clock Testing	ITU-T G.8273.4
PRTC Testing	ITU-T G.8272
time Receiver Testing	ITU-T G.8273.2
eEEC/EEC Testing	ITU-T G.8262.1/G.8262
Announce Message Delay Measurement	ITU-T G.781.1 (APP III)

SyncE Applications – ITU-T G.8262.1/G.8262 (Wander)

The Paragon neo-S supports full SyncE testing to ITU-T G.8262.1/G.8262 including Wander Tolerance, Wander Transfer, Wander (Noise) generation, Pull-in, Hold-in and Pull-out ranges, Frequency Accuracy and Phase Transient.



The Calnex Analysis Tool (CAT) provides powerful insight into network and device performance. All your measurement results are now in one place, and you can view multiple graphs simultaneously for easier correlation of your results. Plus, with enhanced graphics, it's easy to evaluate metrics such as MTIE and TDEV against ITU-T and O-RAN masks.



Application	Paragon neo Tx	Paragon neo Rx
SyncE Wander (noise) Generation	Wander free	Measure Wander
SyncE Wander (noise) Tolerance	Apply Wander	Check ESMC
SyncE Wander (noise) Transfer	Apply Wander	Measure Wander
SyncE Short Term Phase Transient	Break line or set ESMC QL=DNU	SyncE TIE, MTIE

PTP Performance Summary

- Capture and decode PTP packets for analysis and Time Error testing
- PTP clock emulation, plus the Paragon neo-S unique conformance test application, removes uncertainty and maximizes test repeatability – essential for validating new, high-accuracy 5G network devices
- Automatic test of PTP profile compliance for simple and reliable verification against standards-based or user-defined profile configurations

SyncE Performance Summary

- Prove SyncE wander performance to ITU-T G.8262.1/G.8262
- Evaluate MTIE/TDEV pass/fail results to ITU-T G.8262.1/G.8262 masks
- Check ESMC (SSM) messaging to ITU-T G.8264
- Test SyncE jitter performance to ITU-T G.8262.1/G.8262 at NRZ rates

Technical Specifications

Product		
Optical Interfaces (all optional)	NRZ	
	100MbE	SFP
	1GbE	SFP
	10GbE	SFP+
	25GbE	SFP28
	40GbE	QSFP+
	50GbE	QSFP28
	100GbE	QSFP28
	100GbE	QSFP28 DCO
	PAM4 112G	
	200GbE	QSFP112
	400GbE	QSFP112
	800GbE	QSFP112
	800GbE	QSFP112-DD
	Passive DAC supported on all NRZ line rate interfaces	
Electrical Interfaces	1000/100 BASE-T: RJ45	
External Reference Clocks	Lock internal timing reference to external reference	
	External reference inputs: 2.048 MHz, 10 MHz, T1 BITS clock (1.544 Mb/s), E1 MTS (2.048 Mb/s)	
Internal Reference Clock	Frequency stability over temperature – better than ±1 x 10 ⁻⁹	
	Short term phase stability – better than 500 ps	
Clock Reference Output Port	10 MHz/2.048 MHz Reference Output (BNC)	
Phase Measurement	1 pps – BNC (unbalanced)	
	1 pps – RJ48 (balanced)	
Frequency measurement	BNC (unbalanced)	
	RJ48 (balanced)	
1 pps + ToD Reference Input	1 pps Unbalanced Input (BNC), 1 pps Balanced Input + ToD (RJ48)	
	ToD format: CCSA, ITU-T, NMEA	
1 pps + ToD Reference Output	1 pps Unbalanced Output (BNC), 1 pps Balanced Output + ToD (RJ48)	
	ToD format: CCSA, ITU-T, NMEA	
Mechanical Data		
Dimensions(w x h x d)	44.2 x 22.2 x 53.7 cm	
Weight	20.5kg	

Technical Specifications continued

General	
PC/Mac or Tablet Control Interface	Web-based GUI with built-in controller enables use of any PC or Android Tablet with any browser with screen resolution of 1024 x 768 pixels. RJ45 LAN connection to instrument
Workflow	Graphical test-case driven workflow with real-time status and results
	Stimulus/Response test configuration tool
	Detailed configuration options also available
Remote Control	Scripting via TCL, Perl and Python
	Automatic Script Recorder for TCL and Python
	Compatible with Calnex Test Sequencer (CTS) for creation/use of specific or user-defined test plans
PTP	
Standards	IEEE 1588
	G.8273.2 including Class-C and Class-D devices
	G.8272 including Class-B devices
	All relevant G.826x/827x standards
Supported Profiles	IEEE 1588v2 and ITU-T G.8275.1, G.8275.2, G.8265.1
PTP Time Error Measurement Accuracy	Better than 1 ns for NRZ optical interfaces ¹ / Better than 5 ns for PAM4 optical and electrical interfaces ²
timeTransmitter/timeReceiver Emulation	Emulate PTP timeTransmitter with full parametric control
	Emulate PTP timeReceiver
	Add Time Error patterns e.g. G.8273.2, G.8271.1, G.8271.2, G.8261, user-defined
Time Error Metrics	Built-in (CAT) software including industry-standard ITU-T pass/fail masks with clear pass/fail indication
	Time Error (2Way and 1Way) – packet selection and filtering as per ITU-T specifications cTE, dTE, etc.
PTP Packet Analysis	Decode and display PTP Fields with PFV
	Additional options with full PFV licence: Display pass/fail to standards-based or user-defined rules; report generation capability)

¹Except 100 MbE: 5 ns

²Except 1 GbE (15 ns)

Technical Specifications continued

SyncE	
Jitter/Wander Measurement	ITU-T G.8262.1, G.8262, O.174. Jitter/Wander Generation, Transfer, Tolerance, Phase Transient, built-in freq. offset, sinusoidal/MTIE/TDEV Wander generation. Jitter generation/ tolerance measurement on NRZ lines only
Wander Analysis	Built-in (CAT) software including industry-standard ITU-T pass/fail Masks with clear pass/fail indication
	ITU-T Masks: G.8261, G.8262, G.8262.1, G.8261.1
	Wander Measurements: TIE, MTIE, TDEV, clock FFO
ESMC (SSM) Features	Decode ESMC messages to ITU-T G.8264 and graph/plot Quality Level (QL) changes graphically (bi-directional)
	Generate ESMC (SSM) packets as per ITU-T G.8264. Enhanced SSM fully supported
Phase Wander Measurement Resolution	250 ps



Contact Us: +1 844 GO VIAVI | (+1 844 468 4284). To reach the VIAVI office nearest you, visit viavisolutions.com/contact

© 2026 VIAVI Solutions Inc. Product specifications and descriptions in this document are subject to change without notice. Patented as described at viavisolutions.com/patents

calnex-paragonneos-ds-hse-nse-ae
30195225 900 1026

viavisolutions.com

Calnex Paragon neo-S is a product of Calnex Solutions plc.