

E138FB65-APC Smart OTDR

The lightweight and compact P2P Metro and FTTx/PON 1310,1550 and filtered 1650nm Smart OTDR speeds and optimizes field testing of metro and access optical networks—with a tailored OTDR interface and automatic analysis that any technician can understand. The latest B variant unit with 40dB dynamic range. We have available 17 high specification units which include built in broadband Power Meter, Visual Fault Locator, WiFi and Smart Access Anywhere remote connectivity



Complete the [request a quote form](#) now quoting product **E138FB65-APC-ENC**

Units supplied calibrated with 12 months warranty

Included items:

| Catalogue no. | Description |
|------------------|--|
| E138FB65-APC-ENC | SMARTOTDR 100B 1310/1550 AND FILTERED 1650NM - SC/APC AND LIPO |
| E10PM | OPTICAL POWER METER OPTION FOR SMARTOTDR |
| E10VFL | BUILT-IN VFL OPTION FOR SMARTOTDR AND OPTIMETER |
| E10WiFi | BUILT-IN WIFI OPTION |
| SAA-100-L2 | SMART ACCESS ANYWHERE |
| FBPP-SCASE2 | Large Soft Shoulder Carrying Case |
| E20PWMC | AC/DC Power supply |
| E10LIPO | LITHIUM POLYMER BATTERY |