

Specification Sheet

# VIAVI

## CX300

### ComXpert

### General Specifications

<b>General</b>	
<b>Display</b>	
Size	10 in (25.4 cm)
<b>Timebase</b>	
Accuracy	0.02 ppm (0°C to 50°C)
Aging	±1 ppm/year
Warm-up time	3 minutes: within ±0.01 ppm
Accuracy with GPS	±25 ppb (GPS Lock) ±50 ppb (Hold over 72 hours)
External Reference	10 MHz
<b>RF Generator</b>	
<b>Frequency</b>	
Range	100 kHz to 3GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
Resolution	1 Hz
Accuracy	Same as timebase
<b>Output Level</b>	
RF Duplex Port Range	-140 dBm to -30 dBm (10 MHz to 1 GHz); -37 dBm for AM and Complex modulation
RF Output Port Range	-130 dBm to +17 dBm (10 MHz to 1 GHz); +10 dBm for AM and Complex modulation
Resolution	0.1 dB
Accuracy	±1.0 dB (output level > -120 dBm, 1 MHz to 6 GHz) ±2.0 dB (output level ≥ -130 dBm, 1 MHz to 6 GHz) ±1.0 dB typical
Bandwidth	100 MHz
<b>VSWR</b>	
RF Duplex Port	≤11 (1 MHz to 1 GHz); <1.2 (1 GHz to 6 GHz)
RF Output Port	≤1.4 (1 MHz to 1 GHz); <1.5 (1 GHz to 6 GHz)
<b>Spectral Purity</b>	
Phase Noise	-112 dBc/Hz at 10 kHz offset at 500 MHz -110 dBc/Hz at 10 kHz offset at 1000 MHz
Harmonics	-35 dBc
Non-Harmonics	-45 dBc

Residual AM	<0.1% rms
Residual FM	<3 Hz rms 300 Hz to 3 kHz
<b>Analog Modulation</b>	
<b>Modulation</b>	
Modes	AM, FM, PM, SSB
Frequency Range	20 Hz to 20 kHz
Distortion	<1% THD
<b>AM</b>	
Range	0% to 100%
Resolution	0.1%
Accuracy (internal source)	≤±5% of settings
<b>FM</b>	
Range	0 Hz to 100 kHz
Resolution	1 Hz
Accuracy (internal source)	≤±2.5% of setting with frequency response of ±0.5 dB 20 Hz to 10 kHz
<b>PM</b>	
Range	0 rad to 6.3 rad
Resolution	0.1 rad
Accuracy	<±2.5% of setting with frequency response of ±0.5 dB 20 Hz to 10 kHz
<b>SSB</b>	
Modulation frequency	30 Hz to 20 kHz
Carrier suppression	>70 dB
Sideband suppression	>60 dB
<b>Internal Modulation Sources</b>	
Number of sources	3

<b>Sources</b>	
Waveforms	Sine, Square, DTMF, CTCSS, DCS, Two-Tone, Tone Remote, Tone Sequential
<b>Sine Wave</b>	
Range	20 Hz to 20 kHz
Resolution	0.1 Hz
<b>Square Wave</b>	
Range	20 Hz to 20 kHz
CTCSS tone	Tone 1 (67) to Tone 50 (254.1) Hz
Distortion	THD <1.0%
Frequency Response	Level flatness $\leq 0.5$ dB 20 Hz to 10 kHz
<b>RF Receiver</b>	
<b>Frequency</b>	
Range	9 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
<b>Maximum Input Level</b>	
RF Input Port Maximum Input Level	+27 dBm (500 mW) max preamp and frequency $\geq 1$ MHz +13 dBm (20 mW) max preamp on or frequency <1 MHz
RF Duplex Port Maximum Input Level	+47 dBm (50 Watts) continuous, + <35°C +51 dBm (125 Watts) Cyclical (Max "ON" of 30 sec and Min "OFF" for 90 sec) for power levels >50 Watts
Shutdown	Alarm sounds (no auto shutdown)
<b>VSWR</b>	
RF Duplex Port	$\leq 1.2$ (100 kHz to 1 GHz)
RF Input Port	$\leq 1.6$ (100 kHz to 1 GHz) with 10 dB input attenuation
<b>Harmonic Response</b>	
Spurious Response	Input related $\leq -65$ dBc typical Non-input related $\leq -95$ dBm typical
Phase Noise	-112 dBc/Hz at 10 kHz offset at 500 MHz -110 dBc/Hz at 10 kHz offset at 1000 MHz
Dynamic Range	$2/3 * (TOI - DANL) = 109$ dB
TOI	+20 dBm (0 atten), >+1 dBm (preamp), 1 MHz to 1 GHz
DANL	1 Hz RBW @ 1 GHz; <-144 dBm (0 atten), <-162 dBm (preamp)
<b>Sensitivity</b>	
Analog	10 dB SINAD, <-105 dBm with preamp (300 Hz to 3 kHz audio filter, 2.5 kHz FM deviation, 12.5 kHz IF BW)
Bandwidth	100 MHz (wideband VSA), 8 MHz (narrowband)
RF Bandpass Filter (IF Filters)	5 kHz, 6.25 kHz, 8.33 kHz, 10 kHz, 12.5 kHz, 25 kHz, 30 kHz, 100 kHz, 300 kHz
<b>Power Meter</b>	
<b>Frequency</b>	
Range	100 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
Measurement Modes	RMS, average RMS, minimum, maximum

Bandwidth	5 kHz, 6.25 kHz, 8.33 kHz, 10 kHz, 12.5 kHz, 25 kHz, 30 kHz, 100 kHz, and 300 kHz
<b>Level</b>	
RF Duplex Port	-20 dBm to +51 dBm
RF Input Port	-60 dBm to +10 dBm
<b>Accuracy</b>	
RF Duplex Port	$\pm 0.4$ dB (1 MHz to 1 GHz); $\pm 0.6$ dB (1 GHz to 6 GHz)
RF Input Port	$\pm 0.8$ dB (1 MHz to 1 GHz), $\pm 0.9$ dB (1 GHz to 6 GHz)
<b>RF Error Meter</b>	
<b>Frequency</b>	
Range	100 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
Resolution	1 Hz
Accuracy	Frequency Reference
<b>Input Level Range</b>	
RF Duplex Port	-20 dBm to 51 dBm
RF Input Port	-60 dBm to +17 dBm (-80 dBm to -20 dBm w/ pre-amp)
<b>Analog Demodulation Measurements</b>	
<b>FM</b>	
Modes	RMS, $RMS * \sqrt{2}$ , +PK, -PK, $\pm PK/2$
Measurement Range	0 Hz to 75 kHz
Accuracy	$\pm 1.0\%$ for rate $\geq 1.5$ kHz and $\leq 3$ kHz $\pm 2.0\%$ otherwise
FM Distortion	$\pm 0.5\%$ for rate $\leq 3$ kHz $\pm 1.0\%$ otherwise
Residual FM	$\leq 3$ Hz (300 Hz to 3 kHz) and frequency <1 GHz
AF Frequency Range	10 Hz to 20 kHz
<b>AM</b>	
Modes	RMS, $RMS * \sqrt{2}$ , +PK, -PK, $\pm PK/2$
Measurement Range	0% to 100%
Accuracy	$\pm 1.0\%$ for rate $\geq 1.5$ kHz and $\leq 3$ kHz $\pm 2\%$
AM Distortion	$\pm 0.5\%$ for rate $\leq 3$ kHz $\pm 1.0\%$ otherwise
AF Frequency Range	10 Hz to 20 kHz
Residual AM	<0.1% (300 Hz to 3 kHz)
<b>PM</b>	
Range	0 radians to 6.3 radians
Resolution	0.01 rad for $\leq 5$ rad 0.1 rad for >5 rad
Accuracy	$\pm 2.0\%$ , $\pm 1.0\%$ (rate 1.5 kHz to 3 kHz)
<b>SSB</b>	
Modes	SSB-USB, SSB-LSB
Measurement Range	Frequency error, Power (RMS), Power (PEP)

<b>Audio and Demodulation Meters</b>	
<b>Distortion Meter</b>	
Frequency Range	50 Hz to 10 kHz
Measurement Range	0% to 100%
Accuracy	<3% of reading +0.1% distortion, 1% to 20%
<b>SINAD Meter</b>	
Frequency Range	50 Hz to 10 kHz
Measurement Range	0 dB to 63 dB
Accuracy	<±1 dB
<b>S/N Meter</b>	
Frequency Range	50 Hz to 10 kHz
Measurement Range	0 dB to 63 dB
Accuracy	<1 dB
<b>AF Counter</b>	
Frequency Range	50 Hz to 10 kHz
Accuracy	Timebase ±1 Hz
<b>AF Tones Analyzer</b>	
Modes	DTMF, DCS, CTCSS, Two-Tone, Tone Sequential, Tone Remote
<b>Audio Level Meter</b>	
Input Impedance	100 k $\Omega$ , 600 $\Omega$
<b>Level</b>	
Range	0 Vrms to 30 Vrms
<b>Audio Analyzer</b>	
Frequency Range	DC to 100 kHz
Frequency Resolutions	0.8 Hz to 2.4 Hz RBW
FFT Windows	Flat top, rectangular, Hamming, Hann, Blackman-Harris
<b>Level</b>	
Range	50 mVrms to 30 Vrms
Accuracy	±5% (Audio) ±1% (DC)
<b>Audio Filters</b>	
Lowpass	300 Hz, 3 kHz, 3.4 kHz, 5 kHz, 15 kHz, 20 kHz
Highpass	20 Hz, 50 Hz, 300 Hz
Other	C-MSG, CCITT, A-Weighted, C-Weighted
De-emphasis	75 $\mu$ s, 750 $\mu$ s
<b>FFT / Channel Analyzer</b>	
Span	2 kHz to 8 MHz
IF Bandwidth	10 MHz
RBW	1 Hz to 50 kHz
Detector	Normal, positive peak, negative peak, sample, average (RMS)

Accuracy	RF Duplex Port: ±0.7 dB (1 MHz to 1 GHz), ±1 dB (1 GHz to 6 GHz) for level >-10 dBm RF Input Port: ±1.0 dB (1 MHz to 1 GHz), ±1.1 dB (1 GHz to 6 GHz) for level >-50 dBm
<b>Spectrum Analyzer</b>	
Frequency Range	9 kHz to 3 GHz (Standard) 3 GHz to 6 GHz (CX300-F6GHz)
RBW Range	100 Hz to 5 MHz
Span Range	0 Hz to (9 kHz to max frequency of each band)
VBW Range	100 Hz to 5 MHz
Sweep Time Range	0.4 ms to 1000 s
Spurious Free Dynamic Range	≥80 dB
Display Range	1 dB/div to 20 dB/div with 10 divisions
Trigger	Free run, external
DANL	<-142 dBm (0 atten), <-162 dBm (preamp)
<b>Zero Span Analyzer</b>	
<b>Sweep Time</b>	
Range	24 $\mu$ s to 200 s
<b>Tracking Generator</b>	
Output Ports	RF Output Port, RF Duplex Port
<b>Level</b>	
Range	Same as RF Generator
Accuracy	Same as RF Generator
<b>I/Q Recorder</b>	
<b>Sample</b>	
Length	4 Msamples
Rate	Variable to support up to 100 MHz of analog bandwidth
<b>Trigger</b>	
Trigger Source	Free run
<b>AF Generator</b>	
<b>Output</b>	
Impedance	<4 $\Omega$
Max Output Current	100 mA
<b>Frequency</b>	
Range	0 Hz to 100 kHz
Resolution	0.1 Hz
Accuracy	Timebase
<b>Level</b>	
Range	0 Vpk to ±8 Vpk into 600 $\Omega$
Accuracy	±2% (level ≥200 mV and frequency from 20 Hz to 20 kHz)
<b>Distortion</b>	
THD+N	<-75 dB for frequency 1 kHz and level 1 Vrms
AF Composite Signals	Sine, Square, DTMF, DCS, Two-Tone, Tone Remote, Tone Sequential

<b>Oscilloscope</b>	
<b>Display</b>	
Traces	2
Markers	6
<b>Horizontal</b>	
Sweep per div	20 $\mu$ s to 1 s/div
Accuracy	<2%
<b>Vertical</b>	
Range	0.1 mV/div to 20 V/div
Accuracy	<5%
Bandwidth	100 kHz
Input Range	20 mV to 30 Vrms (42.4 Vpk)
Coupling	AC, DC
Input Impedance	300 $\Omega$ , 600 $\Omega$ , 100 k $\Omega$ single ended, $\pm$ 1% shunted by <300 pF 200 k $\Omega$ differential, $\pm$ 8%
<b>Trigger</b>	
Modes	Single, Normal, Automatic, Free run
<b>Digital</b>	
Modes	P25, P25 Phase 2
<b>P25 Measurements</b>	
<b>Accuracy</b>	
Modulation Fidelity	<5% of reading (2.5% to 12%)
Symbol Deviation	$\pm$ 1%
Frequency Error	Timebase $\pm$ 0.5 Hz
Symbol Rate Error	Timebase $\pm$ 0.1 ppm

## Environmental / Physical

Weight	15 lbs (6.8 kg)
Temperature, Not Operating	-40°C to +71°C Note: Battery must not be subjected to temperatures below -20°C, nor above +60°C
Temperature, Operating	0°C to 50°C (battery removed)
Relative Humidity	95% RH (non-condensing)
Altitude	4600 m
Vibration	MIL-PRF-28800F Class 3
Shock, functional	MIL-PRF-28800F Class 3
Bench handling	MIL-PRF-28800F Class 3
Transit Drop	MIL-PRF-28800F Class 3
<b>Battery</b>	
Type	Lithium Ion, 14.4 V, 6.8 Ah
Operating Time	2.3 hours typical with 2 batteries
Battery Charging Limits	0°C to 45°C (32°F to 113°F) $\leq$ 85% RH
<b>Compliance</b>	
EMC	IEC/EN 61326-1:2006, CISPR11:2009 +A1:2010
Safety	EN 61010-1, 3rd Edition



Contact Us +1 800 835 2352  
AvComm.Sales@viavisolutions.com

To reach the VIAMI office nearest you, visit  
viavisolutions.com/contact

© 2021 VIAMI Solutions Inc.  
Product specifications and descriptions in this document are subject to change without notice.  
CX300-ss-rts-nse-ae  
30187740 900 0921