## Brochure

# VIAVI GC-130 GPS Antenna Coupler

Designed to solve the problem of poor GPS coverage in hangar environments or when a simulated static or dynamic GPS signal is required.

The VIAVI GC-130 GPS Antenna Coupler provides >20 dB of antenna isolation, ensuring outside GPS signals are not seen by the aircraft's GPS receiver when simulating a user defined GPS signal. The coupler mounts directly over the aircraft's GPS antenna.

The GC-130 accommodates the large pattern antennas (up to 14" in diameter) and Controlled Radiation Pattern Antenna (CRPA) used on anti-jam GPS systems, unlike the smaller coupler that is included with the VIAVI GPSG-1000 GPS Simulator. These types of antenna are typically used on military and high performance aircraft that require GPS navigation and anti-jam capability.



#### Features

- Provides >20 dB of antenna isolation
- <1 dB repeatability</li>
- Supports GPS antennas up to 14 inches in diameter

**VIAVI** Solutions

• Rugged design for ramp use

### **Benefits**

- Reliable GPS simulation in hangars and other low coverage areas
- When used with the GPSG-1000 GPS Simulator:
  - Almanac and TOD update when no outside GPS signal is available
  - Sensitivity testing of the GPS system
  - Dynamic GPS simulation to simulate aircraft movement for testing of other aircraft systems
  - Determine latency of the GPS and transponder systems

# **Ordering Information**

#### Versions and Options

142163

Order Number	Description	
141193	GC-130 GPS Antenna Coupler Kit	
Standard Accessories		
141747	GC-130 GPS Antenna Coupler	
141982	Rigid transit case	

Coax cable, 20 ft. TNC

# **Physical Characteristics**

Return Loss

Insertion Loss Repeatability

Isolation

Connector

Coupler		
Diameter	20.0 in. (50.8 cm)	
Height	7.6 in. (19.3 cm)	
Weight:	8 lbs. (3.6 kg)	
Transit Case		
Dimensions	24.9 x 23.7 x 13.1 inches	
	63.25 x 60.2 x 33.27 cm	
General		
Frequency	1575.42 MHz (L1/L1C/E1)	
	>12.0 dB at both the	

antenna under test input

and coupler input 8.1 dB <u>+</u>0.5 dB

<1 dB

>20 dB TNC Female



The GC-130 includes a rigid transit case.

#### Export Control

This product is subject to the Export Administration ("EAR") (15 CFR 730–774) and may not be exported, re-exported or otherwise transferred to a foreign person, or outside the United States without authorization from the U.S. Department of Commerce.



Contact Us +1 800 835 2352 avcomm.sales@viavisolutions.com

To reach the VIAVI office nearest you, visit viavisolutions.com/contact.

© 2021 VIAVI Solutions Inc. Product specifications and descriptions in this document are subject to change without notice. Patented as described at viavisolutions.com/patents GC-130coupler-br-avi-nse-ae 30187489 901 0821

viavisolutions.com