

VIAVI Solutions Calibration Cycles

VIAVI Model by Recommended Calibration Interval (months)	
HCU200	60
IBT-100, 200, 300 ISDN Tester	60
IBT-5, 10, 10U, 20 - ISDN Tester/Analyzer	60
RPM-3000	60
DSL-311, 312, 322	48
DA-3200, 3400, 3600	36
HCU204	36
HST-3000 WB2 SIMs - ANY SIM with WB2 in it	36
MPOLx	36
MSQ 800, 900	36
T-BERD/MTS-5800 mainframe *	36
T-BERD/MTS-6000 mainframe *	36
T-BERD/MTS-8000,-8000E mainframe *	36
T-BERD/MTS Transport Modules (all versions, TM8000-V1,V2,V3,100G/40G; CSAM,MSAM)	36
Network & Service Companion (NSC-100)	36
OBS-15, OBS-55, OBS-550	36
OCC-55, 56, 4056	36
OLA-100, OLA-150, OLA-15B Variable Optical Attenuator, OLA-54, OLA-55	36
OLP-3x, OLP-15C, OLP-16C, OLP-18C, OLP-4057, OLP-55, OLP-57	36
OLP-82, OLP-85, OLP-87	36
OLP-5 OLP-6 and OLP-8 Optical Power Meters - Pocket Sized	36
OLS-3X, OLS-15, OLS-55	36
OLS-5 Optical LED Source	36
OLS-6 Optical Laser Source	36
OMK-14C 15C and 18C	36
OMK-5 OMK-6 Optical Test Kits - Pocket Sized	36
OMK-7 Pocket-Sized Fiber Optic Test Kit	36
ONT-5XX, MTM, Optics Modules	36
OneAdvisor-1000	36
ONX - DSL	36
ORL-55	36
SmartClass Handhelds; All models Ethernet, Home, Triple Play, VDSL, ADSL, T1, E1	36
SmartOTU (OTU-5000/-8000)	36
T-BERD 310 Communications Analyzer	36
TLS-55	36

VIAVI Model by Recommended Calibration Interval (months)	
ANT-10Gig	24
ANT-20 Advanced Network Tester	24
ANT-20E or ANT-20SE	24
ANT-40Gig	24
CAA Module, ONA-800	24
Cell Advisor-Cable & Antenna Analyzer - JD723X, JD724X, JD725X, JD726X	24
COSA-4055	24
HST-3000/CTI/E1/E1-DC/T1/T3 SIM Modules	24
OneAdvisor-800	24
ONT-601, MTM, Optics Modules, ONT-603, 606, 612	24
ONT-8xx, Mainframe and Modules	24
ONX – CABLE ONX-610, 620, 630, 220	24
OSA-155, OSA-1xx, 2xx Modules, OSA-3xx, OSA-5xx	24
OSCA-710	24
OTU-8000 Mainframe (OTU-5000/-8000)	24
RSAM, All models	24
SCU-1800	24

Trilithic Products

DSP Cable Meters; All versions	24
Seeker Leakage products	12
All other Trilithic leakage products	36



* Calibration Cycle for a mainframe matches the calibration cycle of the module(s) installed within. For Example, if an OTDR is installed in a T-BERD/MTS mainframe, then the calibration cycle of the mainframe would be 12 months.

VIAVI Solutions Calibration Cycles

VIAVI Model by Recommended Calibration Interval (months)	
ANT-5 SDH Access Tester	18
EST-120 EST-125 EDT-130 EDT-135 E1 and Data Testers	18
PA-20 PA-25 PF-30 PFA-30 PFA-35 E1 and Data Testers	18
PA-41 Frame/Signaling Analyzer	18
RX30xx series Back reflection meter	15
SWS Modules	15
3500	12
3901	12
3902	12
3515 Family	12
3550 Family	12
3920 Family	12
3SR	12
3ST	12
45TS Family	12
8800 Family	12
ALT-8000	12
APM-424 Family	12
ARINC	12
ATB-7300	12
ATB-7300NG	12
ATB-7300S	12
ATC-1400 Family	12
ATC-5000	12
ATC-600 Transponder Test Set	12
ATC-600A-1, Transponder Test Set	12
ATC-600A-2, Transponder Test Set	12
ATC-601 Transponder Test Set	12
ATC-601-1, Transponder Test Set	12
ATC-601-2, Transponder Test Set	12
AVX-10K	12

VIAVI Model by Recommended Calibration Interval (months)	
C4000-LAN	12
Cell Advisor Family	12
CellAdvisor - Power Sensors - JD731X, JD732X, JD733X, JD734X	12
CellAdvisor - RF Analyzer - JD746, JD786	12
CellAdvisor - Signal Analyzer - JD748X, JD788X	12
CellAdvisor JD7105X	12
CellAdvisor JD745X, JD785X	12
cFPL-A1, cORL-A1	12
CLI-950/1450/1750 Combination Meter	12
CX100, CX300, CX700	12
DSAM Digital Service Activation Meter; All models	12
DTS-3xx Digital Broadcast Test Platform	12
FIREBERD 6000A Communications Analyzer	12
FST-2207 T1/T3 Wireless Module	12
FST-2209 T1/T3 Module	12
FST-2230 E1/Data Communications Module	12
FST-2310 SONET Services Module	12
FST-2802 GE Tester	12
GNSS	12
GPSG-1000	12
HST-3000C Mainframe and Copper Modules	12
IFF-701	12
IFF-7300	12
IFR3251	12
IFR3252	12
IFR4000	12
IFR6000	12
IFR6015	12
LST-1700	12
LT-1000	12
MAP modules	12

Find out more information on Calibrations and VIAVI On-Site Calibrations on our VIAVI [Repair and Calibration](#) website!

*** Calibration Cycle for a mainframe matches the calibration cycle of the module(s) installed within. For Example, if an OTDR is installed in a T-BERD/MTS mainframe, then the calibration cycle of the mainframe would be 12 months.**

VIAVI Solutions Calibration Cycles

VIAVI Model by Recommended Calibration Interval (months)	
MicroStealth MS-1000/-1200/-1300/-1400 Signal Level Meters	12
MLS-800 Family	12
MORL-A11308	12
MTS-5100e/-5200e Field Optical Tester	12
PSD120 Family	12
PSD30 Family	12
PSD300 Family	12
PSD3050	12
PSD340	12
PSD40 Family	12
PSD50	12
PSD60 Family	12
PSD600	12
PSD737	12
PSD747	12
PSD757	12
PSD767	12
PSD90 Family	12
PSDAF	12
PTS	12
RD-301 Weather Radar Test Set	12
RDX3000B Radar Test Set	12
RDX-7708 Radar Test Set	12
RDX-7708B Radar Test Set	12
RDX-7708BR Radar Test Set	12
RDX-7708BRW Weather Radar Bench	12
RDX-7708C Radar Test Set	12
RDX-7708CR Radar Test Set	12
RDX-7708CR Radar Test Set	12
RDX-7708CRW Weather Radar Bench	12
RDX-7708R Weather Radar Bench Test	12

VIAVI Model by Recommended Calibration Interval (months)	
RGS-2000	12
RGS-2000	12
RGS-2000NG	12
SP-737	12
SP-747	12
TCAS-201 TCAS Test Set	12
TE747	12
TEA	12
TS-4530/UPM Interrogator/Transponder	12
TS-4542/UPM Interrogator/Transponder	12
TUA	12
Centest/T3AS Test Systems	No Calibration FV Only
FIT-Cleaning Systems	No Calibration FV Only
FIT-Fiber Test Equipment	No Calibration FV Only
FIT-Probe Microscopes and Displays	No Calibration FV Only
HCU400, 1500	No Calibration FV Only
HSM-1000	No Calibration FV Only
HST-3000 Mainframe and non-Copper Modules	No Calibration FV Only
MAP mainframe	No Calibration FV Only
MVP-200	No Calibration FV Only
Optimeter	No Calibration FV Only
PathTrak Performance Monitoring System	No Calibration FV Only
QT-XXX Test Systems	No Calibration FV Only
SmartClass 4800	No Calibration FV Only
T-BERD/MTS-2000 mainframe*	No Calibration FV Only
T-BERD/MTS-4000 mainframe*	No Calibration FV Only
XGIG	No Calibration FV Only
(FV) Functional Verification -all units	36

Find out more information on Calibrations and VIAVI On-Site Calibrations on our VIAVI [Repair and Calibration](#) website!

* Calibration Cycle for a mainframe matches the calibration cycle of the module(s) installed within. For Example, if an OTDR is installed in a T-BERD/MTS mainframe, then the calibration cycle of the mainframe would be 12 months.